

MYAIR DEHUMIDIFIER

25L | 40L | 80L PER DAY

IN CONTROL OF HUMIDITY

PRODUCT FEATURES



MYA25LDE

MYA40LDE & MYA80LDE

- Compact Design
- Electronic Panel with 24 Hour Timer
- Continuous Drainage
- Displays Humidity % Level
- Casters and Carry Handles
- Full Tank Alarm
- Easy access to components for maintenance (air outlet, water tank, filter)



MODEL	MYA25LDE	MYA40LDE	MYA80LDE
Size (mm)	300 x 215 x 460	481 x 286 x 628	481 x 286 x 628
Packing dimensions (mm)	350 x 265 x 530	517 x 330 x 665	517 x 330 x 665
Power supply	AC 220V/240V, 50Hz	AC 220V/240V, 50Hz/60Hz	AC 220V/240V, 50Hz/60Hz
Power consumption (W)	450	700	1350
Moisture removed (L/day)	25	40	80
Humidity settings (RH%)	30-80	30-90	30-90
Air volume (m3/h)	145	250	380
Water tank capacity (L)	5.5	7.2	7.2
Noise level (dBA)	46	48	50
Recommended use temperature	5-35	5-35	5-35
Refrigerant	R290	R410A	R410A
Net weight (kg)	13	21	24
Gross weight (kg)	14	22.5	25.5



@aom.getbetterair